

## 2H1.5 MINERAL INSULATED CABLE DATA SHEET

<b>Cable reference bare</b>	<b>CC2H1.5</b>	
<b>Cable reference served (LSZH low smoke zero halogen material)</b>	<b>CCM2H1.5</b>	
<b>Manufacturer</b>	<b>Wrexham Mineral Cables</b>	
<b>Cables manufactured to</b>	<b>BSEN 60702-1:2002</b>	
<b>Cable type</b>	<b>Mineral Insulated Cable</b>	
<b>Cable voltage rating</b>	<b>750 VOLTS</b>	
<b>Insulation</b>	<b>Compressed magnesium oxide</b>	
<b>Conductor</b>	<b>Plain annealed copper</b>	
<b>Number of conductors</b>	<b>2</b>	
<b>Nominal conductor mm<sup>2</sup></b>	<b>1.5mm<sup>2</sup></b>	
<b>Current rating</b>	<b>Bare 22.5 (amps)</b>	<b>Served 25 (amps)</b>
<b>Voltage drop</b>	<b>28 (per amp / per metre mv)</b>	
<b>Sheath cross section area</b>	<b>11 (Effective mm<sup>2</sup>)</b>	
<b>Earth Fault Loop Impedance @ 70°C</b>	<b>16.902 (R1 + R2) OHMS / km</b>	
<b>Maximum conductor resistance</b>	<b>12.10 OHMS PER 1000 METRES AT 20°C</b>	
<b>Cable diameter bare / covered</b>	<b>7.90mm Bare</b>	<b>9.60 mm Served</b>
<b>Approximate longest coil</b>	<b>1000m</b>	
<b>Approximate weight per 1000m</b>	<b>Bare 247kg</b>	<b>Served 284kg</b>
<b>Accessories</b>		
<b>Gland size reference:</b>	<b>RGM2H1.5/20</b>	
<b>Plain seal kit</b>	<b>RPS2H1.5</b>	
<b>Earth tail seal kit</b>	<b>RPSL2H1.5</b>	
<b>One hole clip reference Bare and LSZH coated</b>	<b>Bare – RC30</b>	<b>Served – RCHL37 Various colours</b>
<b>Two way saddle reference Bare and LSZH coated</b>	<b>Bare – RS342</b>	<b>Served – RSFL382 Various colours</b>
<b>Shroud</b>	<b>PVC RHG20 Various colours</b>	<b>LSZH – RHGMM20 Various colours</b>
<b>Conductor insulating sleeving (followed by mm size)</b>	<b>Standard sleeving RZP</b>	<b>Extension sleeving RZE</b>
<b>Brass locknuts</b>	<b>RLM 20</b>	
<b>Zinc plated steel lock washer</b>	<b>RLWS 20</b>	
<b>Complete straight through joint</b>	<b>RJMZ 20</b>	