

2L1.5 MINERAL INSULATED CABLE DATA SHEET

Cable reference bare	CC2L1.5	
Cable reference served (LSZH low smoke zero halogen material)	CCM2L1.5	
Manufacturer	Wrexham Mineral Cables	
Cables manufactured to	BSEN 60702-1:2002	
Cable type	Mineral Insulated Cable	
Cable voltage rating	500 VOLTS	
Insulation	Compressed magnesium oxide	
Conductor	Plain annealed copper	
Number of conductors	2	
Nominal conductor mm²	1.5mm²	
Current rating	Bare 20.5 (amps)	Served 23 (amps)
Voltage drop	28 (per amp / per metre mv)	
Sheath cross section area	6.3 (Effective mm²)	
Earth Fault Loop Impedance @ 70°C	18.627 (R1 + R2) OHMS / km	
Maximum conductor resistance	12.10 OHMS PER 1000 METRES AT 20°C	
Cable diameter bare / covered	5.70mm Bare	7.20 mm Served
Approximate longest coil	1500m	
Approximate weight per 1000m	Bare 132kg	Served 156kg
Accessories		
Gland size reference:	RGM2L1.5/20	
Plain seal kit	RPS2L1.5	
Earth tail seal kit	RPSL2L1.5	
One hole clip reference Bare and LSZH coated	Bare – RC22	Served – RCHL28 Various colours
Two way saddle reference Bare and LSZH coated	Bare – RS222	Served – RSFL302 Various colours
Shroud	PVC RHG20 Various colours	LSZH – RHGMM20 Various colours
Conductor insulating sleeving (followed by mm size)	Standard sleeving RZP	Extension sleeving RZE
Brass locknuts	RLM 20	
Zinc plated steel lock washer	RLWS 20	
Complete straight through joint	RJMZ 20	